

CEN-PE-CO HYDRAULIC OIL

A double-inhibited anti-wear hydraulic oil.

OUTSTANDING FEATURES AND BENEFITS:

Cen-Pe-Co Hydraulic Oil is formulated with virgin 100% pure paraffin base oil for superior heat resistance and film strength. It is fortified with anti-wear, anti-foam, anti-rust, and anti-oxidation additives.

Water from condensation is hard to avoid in construction equipment, farm equipment, and other mobile equipment. Typical anti-wear hydraulic oils experience additive breakdown in the presence of water, and often plug filters when water enters the system. Cen-Pe-Co Hydraulic Oil has excellent hydrolytic stability (resists degradation in the presence of water), and excellent wet and dry filterability (exceeds specifications for AFNOR NFE 48-690 and AFNOR NFE 48-691).

Cen-Pe-Co Hydraulic Oil is a superior product that provides longer useful fluid life and longer equipment life.

APPLICATIONS:

Industrial equipment (exceeds Denison HF-1, HF-2, HF-0)
Construction, mining, and other mobile equipment
Farm equipment hydraulic systems that have no clutches or drive gears
Hydraulic pumps
Hydraulic jacks
Applications, other than engines, calling for non-detergent oil

CONTAINERS:

55 gallon drum	20 gallon drum
35 gallon drum	5 gallon pail

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO HYDRAULIC OIL

TYPICAL CHARACTERISTICS:

Viscosity				
SAE	<u>5W</u>	<u>10W</u>	<u>20W</u>	<u>30</u>
SUS @ 210° F.	44	48	57	66
SUS @ 100° F.	160	226	368	531
cSt @ 100° C.	5.3	6.6	9.0	11.5
cSt @ 40° C.	31	44	71	102
Viscosity Index	100	100	100	100
Pour Point (° F.)(ASTM D97)	-30	-25	-20	0