



CEN-PE-CO SYNTHETIC OIL & CEN-PE-CO PV SYNTHETIC BLEND OIL

Cen-Pe-Co Synthetic Oil and Cen-Pe-Co PV Synthetic Blend Oils are designed specifically for turbocharged and naturally aspirated gasoline engines in **Personal Vehicles**—cars, pickup trucks, and SUVs. The only difference in their formulation is Cen-Pe-Co Synthetic Oil is fully synthetic and PV Synthetic Blend uses a blend of synthetic base oil and pure paraffin base oil.

These oils are particularly well suited to TGDI (turbocharged gasoline direct injection) engines.

OUTSTANDING FEATURES AND BENEFITS:

- Formulated to avoid Low Speed Pre-Ignition (LSPI) in TGDI engines
- Extra dispersants for improved cleanliness
- Superior anti-wear performance to prevent timing chain elongation
- Superior oxidation (breakdown) resistance for longer turbo life
- Reduced oil consumption over the life of the engine
- Easy cold weather starting
- Outstanding shear stability (resistance to viscosity breakdown)
- Longer drain protection

EXCEEDS SPECIFICATIONS:

API SN Plus, SN, SM

Although it was not licensed by GM, Cen-Pe-Co Synthetic Oil exceeds the wear requirements of GM's dexos™ 1 Gen 2 (dexos™ 1 2016)

VISCOSITY GRADES:

PV Synthetic Blend Oil
SAE 5W-30
SAE 10W-30

Synthetic Oil
SAE 0W-20
SAE 5W-20
SAE 5W-30

CONTAINERS:

55 Gallon Drum
35 Gallon Drum
20 Gallon Drum
5 Gallon Pail

2 Gallon Jug (4 per case)
1 Gallon Bottle (6 per case)
1 Quart Bottle (12 per case)

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO SYNTHETIC OIL & CEN-PE-CO PV SYNTHETIC BLEND OIL

	Synthetic			PV Synthetic Blend	
Viscosity					
SAE	0W-20	5W-20	5W-30	5W-30	10W-30
cSt 40 C	50	47	65	62	66
cSt 100 C	9.3	8.4	10.4	10.6	10.5
Viscosity Index	171	156	148	162	147
Zinc (PPM)	830	830	830	830	830
TBN	9.2	9.2	9.2	9.2	9.2
Sulfated Ash %	0.9	0.9	0.9	0.9	0.9
Specific Gravity	.86	.86	.86	.85	.85