cenpe co product data

CEN-PE-CO SYNTHETIC MTF

A fully synthetic (non-petroleum) Manual Transmission Fluid designed for extended drain intervals in heavy-duty truck transmissions operating in extreme temperatures.

OUTSTANDING FEATURES AND BENEFITS:

Saves fuel

Longer drain performance (up to 500,000 miles and more)

Superior protection against pitting

Better cleanliness performance

Greater oxidation stability

Easier shifting in cold weather

Reduces gear and synchronizer wear

Reduces maintenance costs and downtime

Excellent foam resistance

Lower copper corrosive wear

Excellent seal compatibility

EXCEEDS PERFORMANCE REQUIREMENTS OF:

API GL-1, MT-1, CD*

Eaton Roadranger® PS-164rev.7

Arvin Meritor 0-81

Mack TO-A+

International TMS-6816

ZF TE-ML 02L

Mil-L-2104D*

*Not recommended in engines

TYPICAL CHARACTERISTICS:

Viscosity

SAE 50 (engine oil)

90 (gear lube)

cSt @ 100° C. 17.5

cSt @ 40° C. 132

Viscosity Index 146 Pour Point -49°F

Flash Point 430°F Specific Gravity 0.86

Color Amber

CONTAINERS:

400 pound drum 250 pound drum 120 pound keg 50 pound pail

1 gallon jug (6 per case)

Central Petroleum Company

11810 Madison Ave. 201 East Lincoln Street Cleveland, OH 44107-0597 Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124

